

10-20 Zone Expansion Unit for NC910F or NC920F Part No. NC910EF, NC920EF



Overview

- Expands the number of zones on an NC910F or NC920F Call Controller by 10 or 20 zones (dependent on model purchased).
- ٠ Housed in an attractive flush mounting plastic enclosure measuring just 214mm x 178mm.
- Includes 10 or 20 Zonal Alarm LEDs capable of indicating Standard and Emergency Calls. Note this expansion controller does not include ٠ on onboard buzzer as audible call indication will come from the master controller it is connected to.
- NC910EF provides 10 extra zones, NC920EF provides 20 extra zones. .
- Innovative slide-in labelling system.
- Optional horizontal (NCBOXAS) and vertical (NCBOXAL) alignment plates available to aid the installation of controllers and expansions units located alongside each other.

More Information

Technical Specifications

T 01942 322744

Quiescent current

0mA (none).

Alarm	current
_	

Indicators

Controls

call, pulse for an Emergency call); Audible call indication will come from the separate call None. 2 Buttons - (A) Reset or inactive ; (B) 'Mute' or 'Call Accept' available via NC910S or NC920S call controller.

Determined by the number/type of field devices connected to the call controller/system.

Green Power on LED; 10 (NC910EF) or 20 (NC920EF) red Zonal Alarm LEDs (lit steady for a Standard

E sales@c-tec.co.uk F 01942 829867 W www.c-tec.com



C-TEC, Challenge Way, Martland Park, Wigan, WN5 0LD United Kingdom



Call acknowledgement functionality Yes.

Product dimensions (mm)	214 W x 178 H x 70 D mm (overall). Hole required for flush mounting is 176 W x 162 H x 55 D mm.
Construction & finish	Plastic detachable lid and back box. RAL7035.
IP Rating	IP41.
Weight	1.47kg.
Operating conditions/temperature	-5ºC to +40ºC. Max. relative humidity 95% non-condensing.





